

## **KARERA P**



### Basic product: simple and solid mat for paved / concrete floor

- quad-surface: slip-proof and easy to clean
- · lower side with multisquare-profile: robust and pleasantly soft
- · appropriate softness enhances animal health, productivity and longevity
- · helps to reduce stress and noise
- faster milking through improved parlour entrance and exit and relaxed cows
- through the versatile dimensions and combination possibilities, the most unusually shaped areas can be covered
- simple and fast installation
- suitable for new construction, as well as for renovation
- manure removal with scraper and driving on mats possible\*

### Dimensions: thickness: 21 mm

# 2 sides with puzzle shaped edges - length x width:

170 cm × 95/100/105/110/115/120/125/130 (puzzle seam on wide side)

# 3 sides with puzzle shaped edges - length x width:

170 cm **x** 37.5/47.5/52.5/57.5/62.5/92.5/97.5/102.5/107.5/ 117.5/122.5/127.5 cm (puzzle seam on wide sides and on one long side)

# 4 sides with puzzle shaped edges - length × width:

170 cm × 125 cm

# Scraper manure removal on rubber flooring has already been proven in practice:

In principal we recommend the use of scrapers specifically developed for rubber floors.

For structural alterations it is necessary to adapt the scraper facilities in coordination with the scraper manufacturer, according to the KRAIBURG guidelines for manure scrapers.\*

**Important:** check the scraper at least once a year and grind off the sharp edges!

#### Your KRAIBURG dealer:





quad-surface: slip-proof and hygienic



lower side: multisquare-profile



KRAIBURG fastening system: extremely sturdy, rounded off and flush with the mat



KARERA P in the walking alley



## **Driving over:**

KARERA P can be driven on with standard equipment such as farm yard loader or tractor with authorized pneumatic tyres at the recommended inflation pressure up to max. 4 bar. (Notice: drive with due care and steer in large radius!\*


#### Installation:

easy and fast installation with KRAIBURG fastening system (part of delivery)\*


- \* Please take notice of the corresponding KRAIBURG specifications and installation instructions with useful advice and tips.
- >The products presented here should only be used for the mentioned applications. Technical specifications are subject to alterations. All sales are subject to our General Terms and Conditions. Legal basis is the German version of the document.



KARERA P in the milking parlour



Installation example: walking alley with center guidance



Installation example: further areas, 3 sides / 4 sides puzzle

Tolerances:

thickness:

length + width:

+3/-2 mm +/- 1.5 % (DIN ISO 3302-1 tolerance class M4) The tolerances also apply within the mat and when installed.